

APLITAPE 4000

HEAVYWEIGHT PAPER APPLICATION TAPE

TECH DATA SHEET

4000 is standard weight saturated paper coated with a very low tack rubber adhesive designed specifically as a protective masking of wide format digital graphics and large vinyl graphics.

PHYSICAL SPECIFICATIONS

Adhesive	Rubber-based
Color	White/Translucent
Caliper <i>facestock</i>	100-113 microns (4.0 -4.5 mils)
Caliper <i>facestock + adhesive</i>	125-138 microns (5.0 - 5.5 mils)
Adhesion to Steel*	7 - 9 N/100mm (6 - 8oz.)
Tensile	297 N/100mm (17lb./in)
Elongation	3-4%
Tear Resistance	50
Shelf Life**	1 year
Base	{tag_base}

FEATURES

- Removes easily following graphics application.
- If adhesive touches adhesive, Perform pulls apart easily with no adhesive delamination.
- Works well in either wet or dry applications with no adhesive transfer.

* Adhesion PSTC-101, 1 min dwell on stainless steel

** Stored at 22 OC / 50-55% RH



RTape Corp.
6 Ingersoll Road
South Plainfield, NJ 07080
T [1-800-440-1250](tel:1-800-440-1250)
www.rtape.com

APPLICATIONS

- Premask for large vinyl graphics and digital prints.
- Protective masking for acrylic, high pressure laminates, PETG, polycarbonates and other plastics.

PRINTER PROFILES

Printer profiles are available on rtape.com.

WARRANTY

Tapes are only warranted to be free of defect in workmanship or materials at time of shipment. Manufacturer will replace or credit any material manufacturer deems defective. No acceptance or responsibility for loss, damage, or expense, implies or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability herewith.

RESPONSIVE
RELIABLE
RESOURCEFUL